



HiBoost Consumer Booster HiBoost Dot

Overview

The HiBoost Dot is a triple bands cell phone signal booster that covers over 500-1000 square feet with clear voice and high speed 2G, 3G, 4G voice and data. With our HiBoost Dot, enjoy an innovative mobile signal enhancement solution and capability of remote monitoring.



FCC and IC Fulfillment

- FCC Grant Code OWW and IC Grant Code 10527A for this product series. To get detailed information, go to <https://apps.fcc.gov/oetcf/eas/reports/GenericSearch.cfm>
<http://www.ic.gc.ca/app/sitt/reletel/srch/nwRdSrch.do?lang=eng>



Key Features

- All 2G, 3G and 4G standards are supported
- Remote monitoring via a mobile APP
- Smart AGC function
- Sleek & elegant design and durable construction
- Low interference to cell tower
- FCC and IC certified



Booster Kit Includes

- HiBoost Dot signal booster
- Outdoor Wide Band Directional Antenna with 30 ft Low-loss HiBoost200 Cable
- Indoor Wide Band Panel Antenna with 30 ft Low-loss HiBoost200 Cable
- 5V / 3A, AC/DC Power Supply

Add: 6210 N Belt Line Rd., Ste. 110, Irving, TX 75063 Phone/Fax: (972) 870-5666 E-mail: info@hiboostusa.com
Website: www.hiboost.com

Specification

Working Band	Band 12/17 / Band 13 / Band 5
UL Frequency Range(MHz)	698-716 / 776 – 787 / 824-849
DL Frequency Range(MHz)	728-746 / 746 – 757 / 869-894
Supported Standards	CDMA, LTE standards
Max. Gain	60 dB
Max. Output Power	UL 18 dBm, DL 10 dBm
I/O Port	SMA-Female
Impedance	50 ohm
Environment Conditions	IP40
Dimensions	6.77*4.4*0.75inch/172* 112* 19mm
Weight	≤ 1.32lbs / 0.6kg
Power Supply	Input AC100~240 V, 50/60 Hz, Output DC 5V / 3 A