



Hiboost vehicle booster

C27G-5S-EU

## Description

HiBoost Vehicle booster C27G-5S-EU is a 50dB, ultra wide band cell phone signal booster that provides a complete solution for all vehicles. Improve 2G, 3G and 4G cell phone signal strength for voice and data, especially in poor signal areas. With standardized industrial level design, strict testing and competitive pricing, the C27G-5S-EU provides a superior communication experience with clearer calls and faster data speeds than ever before.



## Key Features

- Supports all 2G, 3G and 4G bands
- Streamlined design
- Quality metal construction, strong and durable
- Good heat dissipation for longevity
- Low interference to cell tower
- Multiple users are supported
- 2 years warranty
- CE certified



## Standard Kit Includes

- C27G-5S-EU mobile signal booster
- Outdoor magnetic antenna with 9.84 ft(3m) cable
- Indoor panel antenna
- Input DC 12-24V, output 5V/3A cigarette lighter with 1.8m USB power cable

---

Address: Herderstr. 94, 40721 Hilden, Germany    Phone: +44 (20) 3239-5808    E-mail: sales@huaptec.eu  
Skype: huaptec.eu    Website: www.hiboost.eu

---



Designed and Produced By Huaptec



## Specification

RF Parameter	Uplink	Downlink
Frequency Range	800MHz	791~821MHz
	900MHz	925~960MHz
	1800MHz	1710~1785MHz
	2100MHz	2110~2170MHz
	2600MHz	2620~2690MHz
Max .Gain	50dB	
Max. Power	25dBm	8dBm
<b>Electrical Parameter</b>		
Power Supply	Input DC 12~24V, output DC 5V/3A	
Input & Output Impedance	50 ohm	
<b>Mechanical Parameter</b>		
I / O Port Type	SMA-Female	
<b>Environment Parameter</b>		
Operating Temperature	-45°C~+55°C	
Storage Temperature	-40°C~+80°C	
Relative Humidity	95%	
Barometric Pressure	55 kPa - 106 kPa	
Environment Conditions	IP40	