



HiBoost Consumer Booster HiBoost Zoom

Overview

The HiBoost Zoom is a wide band cell phone signal booster that covers over 500-3000 square feet with clear voice and high speed 2G, 3G,4G voice and data. With our HiBoost Zoom, enjoy an innovative mobile signal enhancement solution and capability of remote monitoring.





FCC and IC Fulfillment

- FCC Grant Code OWW and IC Grant Code 10527A for this product series. To get detailed information, go to https://apps.fcc.gov/oetcf/eas/reports/GenericSearch.cfm
 https://www.ic.gc.ca/app/sitt/reltel/srch/nwRdSrch.do?lang=eng
- FCC and IC approved this equipment for use with all US & Canadian carriers



Key Features

- · All 2G, 3G and 4G standards are supported
- Remote monitoring via a mobile APP
- MGC + Smart AGC function
- Sleek & elegant design and durable construction
- · Low interference to cell tower
- · FCC and IC certified



Booster Kit Includes

- HiBoost Zoom signal booster
- Outdoor Wide Band Directional Antenna with 30 ft Low-loss HiBoost200 Cable
- · Indoor Wide Band Directional Panel Antenna with 50 ft Low-loss HiBoost200 Cable
- 12V / 3A, AC/DC Power Supply

Add: 6210 N Belt Line Rd., Ste. 110, Irving, TX 75063 Phone/Fax: (972) 870-5666 E-mail: info@hiboostusa.com Website: www.hiboost.com



Specification

Working Band	Band 12/17 / Band 13 / Band 5 / Band 25/2 / Band 4
UL Frequency Range(MHz)	698-716 / 776 – 787 / 824-849 / 1850-1915 / 1710-1755
DL Frequency Range(MHz)	728-746 / 746 – 757 / 869-894 / 1930-1995 / 2110-2155
Supported Standards	CDMA, WCDMA, GSM, EDGE, HSPA+, EVDO, LTE and all cellular standards
Max. Gain	60 dB
Max. Output Power	UL 18 dBm, DL 10 dBm
MGC (Step Attenuation)	≥ 25 dB / 1 dB step
I/O Port	N-Female
Impedance	50 ohm
Environment Conditions	IP40
Dimensions	192* 115* 43mm
Weight	≤ 3.3lbs / 1.5kg
Power Supply	Input AC100~240 V, 50/60 Hz, Output DC 12 V / 3 A