

The HiBoost Travel 3.0 Truck is a 50dB, ultra wide band cell phone signal booster that provides a cellular signal solution for truck. It can improve 2G, 3G, 4G LTE and 5G cell phone signal quality and coverage in voice, text and internet speed for areas with poor signal. With standardized industrial-grade design, upgraded performance and strict testing, Travel 3.0 Truck provides a superior signal experience with clearer calls and faster data speed than ever before!











Outside Omni Antenna



Inside Panel Antenna



Outside 15ft Cable



DC Power Supply





- Supports all US and Canadian carriers
- Compatible with 3G, 4G LTE and 5G DSS cellular standards
- User-friendly remote monitoring via Signal Supervisor app
- Good heat dissipation for longevity
- Multiple users/devices are supported
- Well adapted to complicated scenes
- Timely and reliable technical support via phone, email and online chat
- 3 years warranty
- FCC and IC certified

## **Specification**

UL Frequency Range	698-716 / 776 – 787 / 824-849 / 1850-1915 / 1710-1755
DL Frequency Range	728-746 / 746 – 757 / 869-894 / 1930-1995 / 2110-2155
Max Gain	50 dB
I/O Port	RPSMA-K / SMA-Female
Impedance	50 Ω
<b>Environment Conditions</b>	IP40
Weight	≥ 2.6 lbs / 1.2 kg
Dimensions	6.5 x 4.7 x 1.9 in
Power Supply	Input DC12-24V, Output DC12V-24V/3A Input AC100-240V/1.5A, Output DC12V/3A