

# User Manual

For Vehicle

Travel 2.0 Car

Travel 2.0 RV

Travel 2.0 Truck

3150 Premier Drive, Suite 130,  
Irving, TX 75063  
(972) 870-5666  
service@hiboost.com  
www.hiboost.com





# CONTENTS

Package Content.....	01
Introduction .....	04
Pre-Installation Instructions.....	05
App Assisted Installation.....	11
Troubleshooting Guide .....	22
Technical Specifications.....	23
FCC and IC Statements.....	24
Return and Warranty Policies.....	26

Travel 2.0 Car



Booster



Outside Magnetic Antenna



Inside Panel Antenna



DC Power Supply



Other Accessories  
to fix the booster and antenna

# Package Content

## Travel 2.0 RV



Booster




Outside Omni-Directional Antenna



Inside Magnetic Antenna



Outside 26ft Cable



15.74in pole \*2, Side-Exit Adapter, Spring, Mounting Accessories



Power Supply



DC Power Supply



Other Accessories to fix the booster and inside antenna

# Package Content

## Travel 2.0 Truck



Booster



Outside Omni-Directional Antenna



Inside Panel Antenna



Outside 15ft Cable



DC Power Supply



15.74in pole \*2, Side-Exit Adapter, Spring, Mounting Accessories



Other Accessories to fix the booster and inside antenna

Note: Available accessories can be purchased through [HiBoost.com](http://HiBoost.com)

Warning: Un-authorized antennas, cables, and/or coupling devices are prohibited by new FCC rules, Please contact FCC for details: 1(888)-CALL-FCC.

# Introduction

Thanks again for purchasing HiBoost cell phone booster. The HiBoost vehicle series is a collection of precision-engineered products that improve cellular reception inside of vehicles by amplifying incoming and outgoing cell phone signals.

HiBoost cell booster's exclusive cloud-based Signal Supervisor mobile application and LED indicator allows users to monitor the live status of HiBoost cell phone signal boosters directly from the LED indicator or remotely from a mobile device anywhere at any time.

If there are any issues while installing a HiBoost cell phone signal booster, please contact the HiBoost technical support team through the following options:

**Online Support:** Create a ticket or chat via Signal Supervisor app

 (972) 870-5666 (M-F from 9 am – 5 pm CST)

 [service@hiboost.com](mailto:service@hiboost.com)

 [www.hiboost.com](http://www.hiboost.com)

## Pre-Installation Instructions

We strongly recommend you to read the user guide completely before you install.

The vehicle booster provides app assisted installation,  
And app installation is unique method provided by HiBoost.

**For more precautions and details to install and use, please follow the Signal Supervisor app.**

App Assisted Installation:

**From Page 11~21.**

It's more convenient and the best part is that the maximum booster gain can be reached.


The app helps you find the best install location





## Then why has HiBoost spent extra big efforts and costs to design app signal meter and LED light indicator to help you install?

Out of many reasons, the most important one is that we would like you to get maximum gain from the vehicle booster, as it is most crucial for you to still get the signals even in quite remote areas, like in mountains or forests.

 As it is known and a big thanks, FCC makes signal boosters legal in 2014 so that every body can install and benefit from the signals;

 But FCC regulations do limit the gain and output power of all consumer boosters to low values in order to avoid any interference to the cell towers;

 Furthermore FCC stipulates that any improper install should trigger immediately further reduction of the booster's already-limited gain and power to protect the towers.

 Therefore, you can understand how important you need to squeeze every last gain from the booster, even 1dB more power is so precious when you suffer from no signals.

HiBoost app signal meter & LED light indicator will help you to fine tune the best power and get as much cover of your spaces.



## General Working Principle:

Before we start any of the two ways, please allow us to spend 4 pages to make you understand how the vehicle booster system works for you.

※ Please do spend sometime to read it fully, as it is crucial to get the best performance.

## How HiBoost booster works


### Travel 2.0 Car



1. Outside antenna receives the signal from nearby cell tower and sends to the booster

2. The booster amplifies the signal and sends it to inside antenna

3. Inside antenna broadcasts it inside the vehicle.



Vice versa, inside antenna receives phone signal and sends to the booster, The booster then amplifies and sends it to outside antenna, Outside antenna sends signal to the cell tower. Then you can make phone calls and do internet streaming.


## Travel 2.0 RV



1. Outside antenna receives the signal from nearby cell tower and sends to the booster

2. The booster amplifies and sends it to inside antenna

3. Inside antenna broadcasts it inside the vehicle.




## Travel 2.0 Truck




2. The booster amplifies and sends it to inside antenna

1. Outside antenna receives the signal from nearby cell tower and sends to the booster

3. Inside antenna broadcasts it inside the vehicle.



## Working Principle in Formula



Out of the Formula:

**Outside Signal:** To be received by outside antenna from cell tower

**Outside Antenna Gain:** The gain of the outside antenna

**Outside Cable Loss:** The loss of the outside cable

**Booster Gain:** The actual working gain of the booster

**Inside Cable Loss:** The loss of the inside cable

**Inside Antenna Gain:** The gain of inside antenna

### For example:

**-70dBm + 5dBi - 2.3dB + 50dB - 1dB + 3dBi = - 15.3dBm (System Output Power)**

Since the figures in **Black** are fixed when you finish the purchase, thus **below RED** figures will play a vital role in successful vehicle install

- **Outside Signal**
- **Booster Working Gain**

And since the vehicle is driving anywhere with uncertain outside signals, the **MAX booster working gain** becomes quite crucial.

So the user guide is focused on: **Get the MAX booster working gain.**

# More notes on how to keep the maximum booster gain

The principle is that we need to avoid the loop back between outside and inside antennas as it reduces the gain.


Measures can be taken to avoid the loop back:

- 1) Increase the distance between outside and inside antennas, generally the same vertical distance generates more loss than horizontal distance.
- 2) Use barriers between outside and inside antennas.

Here are some good and bad solutions for your reference.


※ Please note: This separation is not an absolute mandate. The idea is to isolate the outdoor antenna from the indoor antenna.

✓ Perfect




1. Outside antenna locates at highest position.
2. Enough vertical and horizontal distance between outside and inside antennas.
3. Inside antenna is close to demanded coverage area.

✓ Super



1. Outside antenna locates at highest position.
2. Enough horizontal distance between outside and inside antennas.

✗ Bad



1. Not enough horizontal and vertical distance between outside and inside antennas.

# App Assisted Installation

## Flow Chart of App Assisted Installation



### Step 1: Download the 3rd party mobile apps

We are going to use 3rd party app:

- To find a suitable site to install the booster
- To test the signal strength and quality

There are a variety of resources available online: Opensignal, Cell mapper, Network cell info lite, etc.

Please download them beforehand over Android and / or iOS:



※ You can use either of them to your favor. Here we are using Opensignal and Network Cell Info Lite as first two choices.

## Step 2: Select the installation site

Drive to a place with outside signal below  $-85\text{dBm}$ .

You can use the 3rd party app "Network Cell Info Lite" to test on the site to make sure the signal strength is about less than  $-85\text{dBm}$ . Reasons why you need such a place:

- 1) A proper outside signal will create a clean environment for booster install so that we can adjust the booster to get its maximum gain without influencing from outside signal. Because too strong outside signal, say  $-40\text{dBm}$ , will reduce the working gain itself.
- 2) A place with proper signal is also suitable for performance test after the booster has been installed.



You can also use “Network Cell Info Lite” to measure the signal strength before & after install. The good point of Network Cell Info Lite is that you can see the signal levels. But it seems to be only available for Android.



Network Cell Info Lite



The signal strength requested by the booster system is as below.

SIGNAL STRENGTH	EXCELLENT	GOOD	FAIR	POOR	DEAD ZONE
3G/1X	-70dBm	-70 to -85dBm	-86 to -100dBm	-101 to -109dBm	-101dBm
4G/LTE	-90dBm	-90 to -105dBm	-106 to -110dBm	-111 to -119dBm	-120dBm



Your signal strength is going to be a good indicator of how fast you can download and stream, but for voice, it’s more like “Can I make a call, or not?” If you can make a call you should not care how many bars you have, as long as the call goes through and everyone can hear everyone. Looking at bars is just going to make you cranky.



The reason to test your internet speed is to make sure you’ll be able to stream high-bandwidth movies, like those from Netflix, Hulu, Amazon, and other providers. If your internet speed is too slow, you’ll get choppy video or regular buffering.

## Step 3: Install the booster and antennas


### Travel 2.0 Car

#### **Step 1 Assemble and Mount the Outside Antenna**

##### 1.1 Determine where you would like to set up the outside antenna

Usually, the outside antenna is mounted to the roof of the car near the back.

Note: Please make sure the outside antenna is not placed on the glass. If you cannot make it, please keep the outside antenna as close to the back as possible.



##### 1.2 Fix the outside antenna

The antenna has a built-in magnet. You can fix it directly on the metal roof or use the double-side tape in the accessories.



#### **Step 2 Connect the Outside Antenna to the Booster**

Routing the cable into your car and connect it to the booster.




#### **Step 3 Connect the DC Power Supply to the Booster**



#### **Step 4 Download the Signal Supervisor App, register ID and booster.**

Register an ID first and log in.  
Add the booster to the device list.







### **Step 5 Place Inside Antenna & Connect the Cable**

Place the inside antenna where you would like to cover signal and connect it to the booster.

---



Use the Signal Supervisor to help install

The booster will work at best if the gain reaches 50dB. But if you can't get so, at least ensure the gain on the gauges reaches 46-50dB. If not, please kindly adjust the position of the inside antenna.

---



### **Step 6 Fix the Inside Antenna and the Booster**

Fix the inside antenna with the provided double-side tape.

---



Fix the booster with the provided Hook & Loop.

---




## **Step 1 Assemble and Mount the Outside Antenna**

### **1.1 Determine where you would like to set up the outside antenna**

Usually, the outside antenna is mounted to a ladder at the top of the vehicle vertically and as high as possible so that it can get a good signal.

Note: Please make sure the outside antenna stay below the height limit allowed by law.



### **1.2 Assemble the outside antenna**

1) Insert the cable through the pole and then through the side exit adapter.

2) Screw into place.

Notes:

1) The accessories include 2 poles and you can decide to use 1 or 2 depending on the situation.



### **1.3 Fix the outside antenna**

Use the provided accessories to fix the outside antenna to the ladder.



## **Step 2 Connect the Cable to the Outside Antenna**

Connect the booster and the outside antenna with the 26' cable.



### **Step 3** *Connect the DC Power Supply to the Booster.*

Use power supply or DC power supply.



### **Step 4** *Download the Signal Supervisor App, register ID and booster.*

Register an ID first and log in.  
Add the booster to the device list.



### **Step 5** *Place Inside Antenna & Connect the Cable*

Place the inside antenna where you would like to cover signal and connect it to the booster.



Use the Signal Supervisor to help install

The booster will work at best if the gain reaches 50dB. But if you can't get so, at least ensure the gain on the gauges reaches 46-50dB. If not, please kindly adjust the position of the inside antenna.




### **Step 6** *Fix the Inside Antenna and the Booster*

Fix the inside antenna with the provided double-side tape.



Fix the booster with the provided Hook & Loop.  
Enjoy your boosted signal!




## **Step 1 Assemble and Mount the Outside Antenna**

### **1.1 Determine where you would like to set up the outside antenna**

Usually, the outside antenna is mounted to a rearview mirror. It would be great if you could set it as high as possible.

Note: Please make sure the outside antenna stay below the height limit allowed by law.



### **1.2 Assemble the outside antenna**

- 1) Insert the cable through the pole and then through the side exit adapter.
- 2) Screw into place.

Notes:

- 1) The accessories include 2 poles and you can decide to use 1 or 2 depending on the situation.



### **1.3 Fix the outside antenna**

Use the provided accessories to fix the outside antenna to the rearview mirror.



## **Step 2 Connect the Cable to the Outside Antenna**

Connect the booster and the outside antenna with the 15' cable.



## **Step 3 Connect the DC Power Supply to the Booster.**



**Step 4** *Download the Signal Supervisor App, register ID and booster.*

Register an ID first and log in.  
Add the booster to the device list.

---



**Step 5** *Place Inside Antenna & Connect the Cable*

Please place the inside antenna on the dash or the side of driver's seat.

---



Use the Signal Supervisor to help installation

The booster will work at best if the gain reaches 50dB. But if you can't get so, at least ensure the gain on the gauges reaches 46-50dB. If not, please kindly adjust the position of the inside antenna.

---



**Step 6** *Fix the Inside Antenna and the Booster*

Fix the inside antenna with the provided double-side tape.

---



Fix the booster with the provided Hook & Loop.

Enjoy your boosted signal!

---

#### Step 4: Signal quality test

After reaching the MAX possible gain (50dB or as close to 50dB as possible), fix the outside & inside antennas, and then use the mobile phone to test the effect of phone call and browse the web page or video in the vehicle by 3rd party app Network Cell Info Lite & Open Signal.

\*Notes Again: Just remember that strength and quality are two separate issues. A poor quality “strong” signal can be next to useless, but a clean signal of two bars might be all your device needs.



If it is not ideal, adjust the position of inside or outside antennas, and meantime ensure that the gain remains MAX possible.

When it reaches the ideal test value, the booster, antenna and cable can be firmly installed.

**The installation order is: Outside antenna – Inside antenna – Booster.**

Notes: Please don't expect the vehicle booster system to cover your whole area, because its gain is limited to 50dB by FCC and may further reduce during booster installation and the outside signal is changing all the time during the drive.

### **Step 5: Drive the vehicle to other places to see how it works**

Drive the vehicle to various weak areas to test the performance.

Drive the vehicle to various strong areas to test the performance.

#### **Warm Tips**

If the vehicle is driving to quite remote places where the signal outside is particularly weak and the mobile phone cannot be used, the inside antenna can cling closely to the back of the mobile phone, so that a certain signal can be obtained. This is not a normal operation, but it can help you maintain communication in these particular places.

**Meanwhile, remind you that this method will not help when there is no signal outside the vehicle or the signal is very weak, because the booster must have a signal to boost.**



# Troubleshooting Guide

## LED STATUS INDICATORS

LED STATUS INDICATORS		
ALARM(ISO)	solid blue	normal
	slow flashing blue	slight loopback
	quick flashing blue	loopback
	quick flashing red	booster automatically shut off due to strong loopback/overload
Bluetooth LED	slow flashing blue	bluetooth disconnected
	quick flashing blue	bluetooth connected
Wi-Fi LED	solid blue	wifi disconnected
	slow flashing blue	wifi connected

Common Issues	Troubleshooting Instructions
The vehicle booster is installed but there's still no signal	Check to see if the vehicle is started. Double check connections to make sure none are loose.
The signal is not stable after turning on the booster power	Check that the outside signal is stable by referring to your mobile device and checking your coverage.
The Alarm LED is quick flashing blue or red or off	Check to make sure vehicle is not parked too close to a cell tower.
There is No Power	Check that the booster is turned on and the DC power outlet is plugged into the DC 12V port or lighter adapter

If there are any issues while installing a HiBoost cell phone signal booster, please contact the technical support team through the following channels:

**Online Support:** Create a ticket or chat via Signal Supervisor app

 (972) 870-5666 (M-F from 9 am – 5 pm CST)

 [service@hiboost.com](mailto:service@hiboost.com)

 [www.hiboost.com](http://www.hiboost.com)



# Technical Specifications

RF Parameter		Uplink	Downlink
Frequency Range	LTE(A+B)	698-716MHz	728-746MHz
	LTE(C)	776-787MHz	746-757MHz
	CDMA	824-849MHz	869-894MHz
	PCS	1850-1915MHz	1930-1995MHz
	AWS	1710-1755MHz	2110-2155MHz
Max. Gain			50dB
Max. Power		UL 22 dBm	DL 0 dBm
Electrical Parameter			
Power Supply		Input DC12-24V, Output DC5V/3A	
Input Impedance		50 ohms	
Mechanical Parameter			
I/O Port Type		SMA-Female	
Environment Parameter			
Operating Temperature		-10°C~+55°C	
Storage Temperature		-25°C~+80°C	
Environment Conditions		IP40	

# FCC and IC Statements

## FCC RF EXPOSURE STATEMENT

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. End users must follow the specific operating instruction for satisfying RF exposure compliance. This transmitter must not be colocated or operating in conjunction with any other antenna or transmitte.

## IC RF EXPOSURE STATEMENT

The devices is compliance with RF exposure limits. The minimum distance from body to use the device is 20 CM.

Le présent appareil est conforme aux conformité ou aux limites d'intensité de champ RF. La distance minimale du corps à utiliser le dispositif est de 20 CM.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Re-orient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected
- Consult the dealer or an experienced radio/TV technician for help

Changes or modifications not expressly approved by HiBoost could void the user's authority to operate the equipment. For a complete list of antennas and cables approved for use with these boosters see Authorized Kitting Options

FCC 27.50(d)(4) Statement: Fixed, mobile, and portable (handheld) stations operating in the 1710-1755 MHz band are limited to 1-watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground.

**FURTHER INFORMATION ON SIGNAL BOOSTER END-USE REGISTRATION**

The following links are the currently active contacts for booster registration with U.S. wireless providers:

<https://www.uscellular.com/uscellular/support/fcc-booster-registration.jsp>

[https://www.sprint.com/legal/fcc\\_boosters.html](https://www.sprint.com/legal/fcc_boosters.html)

<https://www.verizonwireless.com/solutions-and-services/accessories/register-signal-booster/>

<https://support.t-mobile.com/docs/DOC-9827>

<https://securec45.securewebsession.com/attsignalbooster.com/>

IC Statement: This device complies with Innovation, Science and Economic Development Canada ICES-003 Compliance Label: CAN ICES-3 (B)/NMB-3(B). Le présent appareil est conforme Innovation, science et développement économique Canada ICES-003 Étiquette de conformité: CAN ICES-3 (B) / NMB-3 (B).

**This is a CONSUMER device.**

BEFORE USE, you MUST REGISTER THIS DEVICE with your wireless provider and have your provider's consent. Most wireless providers consent to the use of signal boosters. Some providers may not consent to the use of this device on their network. If you are unsure, contact your provider.

In Canada, BEFORE USE, you must meet all requirements set out in ISED CPC-2-1-05.

You MUST operate this device with approved antennas and cables as specified by the manufacturer. Antennas MUST be installed least 20 cm (8 inches) from (i. e., MUST NOT be installed within 20 cm of) any person.

You MUST cease operating this device immediately if requested by the FCC (or ISED in Canada) or a licensed wireless service provider.

WARNING. E911 location information may not be provided or may be inaccurate for calls served by using this device.

This device may be operated ONLY in a fixed location (i.e., may operate in a fixed location only) for in-building use.

# Return and Warranty Policies

**30-Day Money-Back Guarantee:** If for any reason the performance of any product is not acceptable, the product may be returned to the reseller within 30-days with proof of purchase. Please contact the customer support team.

**3-Year Warranty:** Signal boosters and kits are warranted for 3 years. We will repair or replace the unit and will cover the cost of delivery back to consumers located within the continental US and Canada. We will only cover shipping to our office if the booster was delivered to you recently, and was delivered defective. Damage caused by the use of non-company power supplies or other accessories is not covered under warranty.

Customers can choose to return the signal boosters and kits directly to the manufacturer at the purchaser's expense with a dated proof of purchase and a Returned Material Authorization (RMA) number supplied by us. RMA numbers may be obtained by contacting customer support at 972-870- 5666 or support @hiboost.com

This warranty does not apply to any signal boosters or kits determined by us to have been subjected to tampering, misuse, abuse, neglect, or mishandling that alters or damages physical or electronic properties.

We are not liable for any Signal Supervisor application network connectivity issues. The cell phone signal booster relies on a strong, continuous and reliable connection to the internet in order to communicate with the cell phone application. For all Signal Supervisor Application related issues, please check your network strength and call our technical support.

Failure to use a surge-protected AC power strip with at least a 1000 Joule rating will void your warranty. Damage caused by lightning is not covered by this warranty.

All of the products that are packaged with other accessory products are intended for resale and used as a single integrated system. Such product kits are required to be sold to the end-users or subsequent reseller as packaged.

